

Connectivity - linear lighting



Product specification

Product name	Housing	Output current range	Output voltage range	Dimming range	DALI power supply max. supply current	Energy metering accuracy	Order code
	mm	mA	V	%	mA	%	EOC
Xitanium SR 36W 0.3-1.0A 54V iso	360x30x21	300-1000	27-54	100-1	52	4	8718696567715
Xitanium SR 75W 0.7-2.0A 54V iso	360x30x21	700-2000	27-54	100-1	52	4	8718696552704
Xitanium 35W 0.08-0.35A 150V SR 230V	360x30x21	80-350	50-150	100-1	52	4	871869669814300
Xitanium 60W 0.08-0.35A 220V SR 230V	360x30x21	80-350	50-220	100-1	52	4	871869669816700
Xitanium 60W 0.08-0.35A 300V SR 230V	360x30x21	80-350	100-300	100-1	52	4	871869669818100
Xitanium 100W 0.25-0.7A 220V SR 230V	360x30x21	250-700	50-220	100-1	52	4	871869669924900
Xitanium 100W 0.15-0.5A 300V SR 230V iXT	425x30x21	150-500	100-300	100-1	52	4	871869669926300
Xitanium 150W 0.2-0.7A 300V SR 230V iXT	425x30x21	200-700	100-300	100-1	52	4	871869669928700
Xitanium SR bridge built-in	204x30x21	N/A	N/A	N/A	52	4	871869671982400
Xitanium SR bridge independent	228x30x21	N/A	N/A	N/A	52	4	871869671984800