

Connectivity - outdoor lighting



Product specification

Product name	Housing	Output current range	Output voltage range	Dimming range	Efficiency @ 100% load	Lifetime @ Tc life	Diagnos- tics via SR interface	DALI power supply via SR interface max power 0.5W	24V power supply 3W average power / 10W peak	Energy metering accuracy	Order code
		mA	V	%	%	hrs				%	EOC
Xitanium SR 12W 0.2-0.7A C133 sXt	C133	200-700	8-32	100-10	83	100.000	•	•	•	1	871869673916700
Xitanium SR 22W 0.2-0.7A C133 sXt	C133	200-700	16-48	100-10	85	100.000	•	•	•	1	871869673918100
Xitanium SR 22W 0.3-1.0A C133 sXt	C133	300-1050	8-32	100-10	85	100.000	•	•	•	1	871869673912900
Xitanium SR 40W 0.2-0.7A C133 sXt	C133	200-700	25-77	100-10	86	100.000	•	•	•	1	871869673914300
Xitanium SR 40W 0.3-1.0A C133 sXt	C133	300-1050	20-54	100-10	86	100.000	•	•	•	1	871869656879800
Xitanium SR outdoor 75W 0.3-1.0A S240 sXt	S240	300-1050	20-100	100-10	88	100.000	•	•	•	1	871869667414700
Xitanium SR outdoor 150W 0.2-0.7A S240 sXt	S240	200-700	90-283	100-10	90	100.000	•	•	•	1	871869656875000
Xitanium SR outdoor 150W 0.3-1.0A S240 sXt	S240	300-1050	70-214	100-10	90	100.000	•	•	•	1	871869667412300

* Standard features: Input voltage range 170-264V, Surge protection DM/CM 6/8kV, SimpleSet, DynaDimmer, Module Temperature Protection

Connectivity - retail lighting



Product specification

Product name	Housing	Output current range	Output voltage range	Dimming range	YellowDot Ready (indoor positioning)	Order code
		mA	V	%		EOC
Xitanium 60W 0.08-0.35A 300V TD16CL 230V	280x30x16	80-350	100-300	100-1	•	871869669890700
Xitanium 100W 0.15-0.5A 300V iXt TDCL 230V	360x30x21	150-500	100-300	100-1	•	871869669858700
Xitanium 150W 0.2-0.7A 300V iXt TDCL 230V	360x30x21	200-700	100-300	100-1	•	871869669888400

* Standard features: Input voltage range 170-264V, Surge protection DM/CM 6/8kV, SimpleSet, DynaDimmer, Module Temperature Protection