

Монетоприемники

Серия HI-07CS, HI-072CS



COIN SPECIFICATION

Diameter: 18mm~31mm
Thickness: 1.2mm ~ 3.0mm

USER EQUIPMENT

Voltage: DC 12V \pm 20%
Currents: 200mA

CPU TYPE + LED + WARNING ALARM

Suit to all coins of diameter & thickness & materials
Time switch function for adjustment
Anti-stringing to protect machine
Connect to meter
2 kinds of CPU control alarm warning setup & lockout function

Серия HI-08CS, HI-0801CS



COIN SPECIFICATION

Diameter: 18mm~31mm
Thickness: 1.2mm ~ 3.0mm

USER EQUIPMENT

Voltage: DC 12V
Currents: 150mA

CPU TYPE

CPU control anti-stringing system
Lockout 3 cycles
Slot coin speed limited
Inhibit: high (+3v~+12v)
low (below +1v)

ANTI-STRINGING CPU SYSTEM SPECIFICATION

LOCKOUT 3 CYCLES AUTO REFLECT

1st time 10sec / 2nd time 10sec / 3rd time 25sec

Серия HI-09FCS



MULTI COIN SELECTOR

1. Accept 8 kinds of coins at the same time.
2. Self-programming without PC.
3. With an Inhibit line for main machine