


## **Product Specification**

Version: 1.0

# BT-0260-V2 BT Printer Combo Adapter



Manufacturer	CC&C Technologies, Inc.	
Issue Date	5 Mar. 2007	



8F, No. 150, Jian Yi Road, Chung Ho City,
Taipei County, Taiwan 235, R.O.C.
Tel: 886-2-8226-5088 Fax: 886-2-8226-5077

#### **Overview**

Featuring Bluetooth wireless technology, BT Printer Combo Adapter creates cable-free printing connections between your desktop PCs and printers.

BT Printer Combo Adapter supports Bluetooth v2.0+EDR and is backward compatible with v1.1 devices. You can connect your computing devices and printers 100 meters away without cables in your working environments, such as home or office.

#### **Features**

- Support Bluetooth Hard Copy Replacement Printing Profile (HCRP)
- Support Bluetooth Serial Port Profile (SPP)
- Support Bluetooth v2.0+EDR
- Operate in 2.4GHz~2.483GHz ISM band
- Bluetooth Class I
- Operating distance of up to 100 meters
- Support both USB and 1284 printer port interfaces
- Three LEDs Indicating:

Power On/Off

Printer Action

Bluetooth Link

Easy operation and setup





## **General Specification**

Product Name	BT Printer Combo Adapter	
Model Name	BT-0260-V2	
Standard	Bluetooth v2.0+EDR	
Frequency Band	2.4~2.4835GHz unlicensed ISM band	
Spread Spectrum	FHSS (Frequency Hopping Spread Spectrum)	
Services supported	SPP and HCRP print services	
RF Output Power	Class 1; 13dBm typical	
Working distance	Up to 100m in free space	
Sensitivity	<-88dBm at < 0.1% BER	
I/O Interface	USB, IEEE-1284	
LED indicator	Power / Bluetooth active /Printing active	
Certification	FCC, CE, BQB	
Environment	Operation temperature: 0 oC ~ + 60 oC	
	Storage temperature: -10 oC ~ +70 oC	
	Humidity: 5 ~ 90% non-condensing	
Dimension	76 (L) x 62(W) x 20(H) mm	



### Dimension

