

BT040AACBHB\$

4.0" Color TFT-LCD video module.

TFT LCD:

1. 4.0 inch TFT LCD panel **BT040AANNH\$**.
2. View angle (U/D/L/R): **35/15/50/50**
3. Resolution: **320*(RGB)*234 (pixels)**,
0.2535 (H) x 0.2640 (V) mm dot pitch.
4. Brightness (cd/m²): **350cd/m² Typical**.
5. Contrast Ratio: **350:1**.
6. Active area: **81.12(H)*361.78(V)** mm.
7. Panel Dimension: **93.0(W)*73.5(H)*3.50(D)**(typ.).

Video Board:

1. Power Requirements: **12.0V DC±10%**.
2. Operating Temperature Range: **0~ +50°C**.
3. Storage Temperature Range: **-10~ +60°C**.
4. Dimension (W x H x T): **73.5*54.6*7.5 mm**.
5. Keyboard (optional): 5 Keys with OSD menu for image quality tuning supported.
6. Input Video: **CVBS*1**.
7. Input impedance: **75Ω**.
8. Video system: **NTSC/PAL/SECAM auto detection**.



Ordering Information:

Part NO.	Option(1) Bracket	Option(2) Host Cable	Option(3) Keyboard(with keyboard cable)
BT040AACBHB352\$	✓	✓	
BT040AACBHB352a\$	✓	✓	✓
BT040AACBHB352b\$		✓	✓
BT040AACBHB352c\$		✓	
BT040AACBHB352d\$	✓		
BT040AACBHB352e\$	✓		✓
BT040AACBHB352f\$			✓

Dimension:

