



20.0×9.8×11.0

# M1B

UL E158859 R50044268  
Patent No.: 02265923.4

Features
<ul style="list-style-type: none"> <li>• DIL Pitch Terminals .High Sensitivity.</li> <li>• Conforms to FCC Part 68 1.5kV Surge and Dielectric 1000VAC.</li> <li>• Fully sealed (immersion cleaning).</li> <li>• High Reliability bifurcated Contact.</li> <li>• Application for Telecommunication Equipment,Office Equipment,Security Alarm Systems,Measuring instruments, Medical Monitoring Equipment,Audio Visual Equipment,Flight Simulator,Sensor Control.</li> </ul>

Ordering Information
<p><b>M1B 12 H A W</b> 1 2 3 4 5</p> <p>1 Part number: M1B 2 Coil rated voltage: DC:3:3V; 5:5V; 6:6V; 9:9V; 12:12V; 24:24V; 48:48V 3 Enclosure: H: Sealed Type 4 Nominal coil power: Nil:0.55W; A:0.4W 5 Contact material: Nil: AgPd; W: AgNi</p>

Contact Data		
Contact Arrangement	2C (DPDT(B-M)) (Bifurcated Crossbar)	
Contact Material	AgPd( Gold clad) AgNi(Gold clad)	
Contact Rating (resistive)	0.01mA/10mV to 1A/24VDC; 0.5A/120VAC	
Max. Switching Power	60W 125VA Min. Switching load: 0.01mA/10mV (Reference Value)	
Max. Switching Voltage	220VDC 250VAC Max. Switching Current:2A	
Contact Resistance or Voltage drop	≤50mΩ Item 4.12 of IEC 61810-7	
Operational Life	Electrical	1A/24VDC: $5 \times 10^5$ (Ag Ni : $1 \times 10^5$ ) 0.5A/120VAC: $2 \times 10^5$ Item 4.30 of IEC 61810-7
	Mechanical	$10^8$ Item 4.31 of IEC 61810-7

**CAUTION:** Relays previously tested or used above 10mA resistive at 6V maximum (DC or peak AC) open circuit are not recommended for subsequent use in low level applications.

Dash numbers	Coil voltage VDC		Coil resistance Ω ±10%	Pick up voltage VDC(max) (70% of rated voltage)	Release voltage VDC(min) (10% of rated voltage)	Coil power W	Operate Time ms	Release Time ms
	Rated	Max.						
M1B-003	3	4.2	16	2.1	0.3	0.56	Approx. 5	Approx. 3
M1B-005	5	7.0	45	3.5	0.5	0.56		
M1B-006	6	8.4	66	4.2	0.6	0.55		
M1B-009	9	12.3	140	6.3	0.9	0.58		
M1B-012	12	17.4	280	8.4	1.2	0.52		
M1B-024	24	34.0	1070	16.8	2.4	0.54		
M1B-048	48	64.9	3900	33.6	4.8	0.59		
M1B-003A	3	4.9	22.5	2.1	0.3	0.4	Approx. 5	Approx. 3
M1B-005A	5	8.1	62.5	3.5	0.5	0.4		
M1B-006A	6	9.7	90	4.2	0.6	0.4		
M1B-009A	9	14.5	203	6.3	0.9	0.4		
M1B-012A	12	19.4	360	8.4	1.2	0.4		
M1B-024A	24	38.9	1440	16.8	2.4	0.4		
M1B-048A	48	77.8	5760	33.6	4.8	0.4		

**CAUTION:** 1.The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.  
2.Pickup and release voltage are for test purposes only and are not to be used as design criteria.

Characteristics		
Electrostatic capacitance		
Between open Contacts	Approx.0.7pF	Item 4.41 of IEC 61810-7
Between coil & Contacts	Approx.1.0pF	Item 4.41 of IEC 61810-7
Between Contact Poles	Approx.0.9pF	Item 4.41 of IEC 61810-7
Insulation Resistance	1000MΩ min (at 500VDC)	Item 7 of IEC 60255-5
Dielectric Strength		
Between open Contacts	1000VAC 1min	Item 6 of IEC 60255-5
Between coil & Contacts	1000VAC 1min	Item 6 of IEC 60255-5
Between Contact Poles	1000VAC 1min	Item 6 of IEC 60255-5
Surge Withstand Voltage		
Between open Contacts	1500V	FCC 68
Between coil & Contacts	1500V	FCC 68
Between Contact Poles	1500V	FCC 68
Shock resistance	Functional:100m/s <sup>2</sup> 11ms; Survival:1000 m/s <sup>2</sup> 6ms	IEC 68-2-27 Test Ea
Vibration resistance	10~55Hz Double amplitude Functional: 1.5mm Survival:5mm	IEC 68-2-6 Test Fc
Terminals strength	5N	IEC 68-2-21 Test Ua1
Solderability	235°C ± 2°C 3 ± 0.5s	IEC 68-2-20 Test Ta method1
Temperature Range	-40~65°C (-40~149 ° F) (-40~70°C for 0.4W Coil)	
Mass	4.5g	

Safety approvals		
Safety approval	UL&CUR	TÜV
Load	1A/24VDC 0.5A/120VAC	1A/24VDC、0.5A/120VAC

Dimensions		mm/inch
<p>Dimensions</p>		<p>Wiring diagram (Bottom view)</p>
<p>Mounting (Bottom view)</p>		
<p>NOTES 1).Dimensions are in millimeters. 2).Inch equivalents are given for general information only.</p>		

