


Xitanium LED drivers - lite programmable Xtreme



Product specification

Product name	Housing	Output current range	Output voltage range	Output power	Dimming range	Efficiency range, max load	Inrush current peak	Inrush current width to 50%	Power factor, 100% load	Power factor, dimmed 50%	Simple-Set	Line-Switch	1-10 V	Dyna-Dimmer lite (1-step)	Dyna-Dimmer (5-step)	Order code
	type	mA	V	W	%	%	A	µs								EOC
Xi LP 22W 0.3-1.0A S1 230V C123 sXt	C123	300-1050	8-32	0.6-22	100-10	87	15	320	0.99	0.97	•		•			8718696 672372 00
Xi LP 40W 0.2-0.7A S1 230V C123 sXt	C123	200-700	25-77	1.8-40	100-10	89	22	250	0.98	0.96	•		•			8718696 675809 00
Xi LP 40W 0.3-1.0A S1 230V C123 sXt	C123	300-1050	20-54	1.5-40	100-10	89	22	250	0.98	0.96	•		•			8718696 672396 00
Xi LP 35W 0.3-1.0A S1 230V C150 sXt	C150	300-1050	20-60	4-36	100-7	87	33	290	0.96	0.86	•		•			8718696 526651 00
Xi LP 70W 0.2-0.7A S1 230V C150 sXt	C150	200-700	50-150	4-70	100-10	90	37	290	0.98	0.96	•		•			8718696 477380 00
Xi LP 70W 0.2-0.7A SL 230V C150 sXt	C150	200-700	50-150	4-70	100-10	90	37	290	0.98	0.96	•	•				8718696 477342 00
Xi LP 70W 0.3-1.0A S1 230V C150 sXt	C150	300-1000	32-100	4-70	100-10	90	37	290	0.98	0.96	•		•			8718696 477403 00
Xi LP 70W 0.3-1.0A SL 230V C150 sXt	C150	300-1000	32-100	4-70	100-10	90	37	290	0.98	0.96	•	•				8718696 477366 00
Xi LP 110W 0.2-0.7A S1 230V C150 sXt	C150	200-700	70-220	6.5-110	100-10	91	37	290	0.98	0.96	•		•			8718696 477465 00
Xi LP 110W 0.2-0.7A SL 230V C150 sXt	C150	200-700	70-220	6.5-110	100-10	91	37	290	0.98	0.96	•	•				8718696 477427 00
Xi LP 110W 0.3-1.0A S1 230V C150 sXt	C150	300-1050	50-160	6.5-110	100-10	91	37	290	0.98	0.96	•		•			8718696 477489 00
Xi LP 110W 0.3-1.0A SL 230V C150 sXt	C150	300-1050	50-160	6.5-110	100-10	91	37	290	0.98	0.96	•	•				8718696 477441 00
Xi LP 165W 0.2-0.7A S1 230V C170 sXt	C170	200-700	100-300	7-165	100-10	93	41	440	0.98	0.96	•		•			8718696 711286 00
Xi LP 165W 0.3-1.0A S1 230V C170 sXt	C170	300-1000	80-235	7-165	100-10	93	41	440	0.98	0.96	•		•			8718696 711309 00
Xi LP 165W 0.5-1.5A S1 230V C170 sXt	C170	500-1500	54-157	7-165	100-10	93	41	440	0.98	0.96	•		•			8718696 711323 00

Surge protection CM/DM 8/6 kV
Input voltage range 220-240 Vac
Tc life 75°C
Lifetime @ Tc life, 90% survivals 100,000 hrs